

Panel mounted receptacle  
Part no. 231A




- screw terminals
- straight

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 32 A            |
| Poles                     | 3 p             |
| Voltage                   | 400 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 67           |
| Flange                    | 85x75 mm        |
| Fixing hole               | 60x60 mm        |
| Weight                    | 266 g           |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>1 MB 141                                 | Amp.<br>Poles | 16  |     |     | 32  |     |     |
|-----------------------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                                                     |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm                                          | a             | 75  | 75  | 75  | 85  | 85  | 85  |
|                                                     | b             | 75  | 75  | 75  | 75  | 75  | 75  |
|                                                     | c             | 60  | 61  | 61  | 70  | 70  | 72  |
|                                                     | d             | 60  | 60  | 60  | 60  | 60  | 60  |
|                                                     | e             | 60  | 60  | 60  | 60  | 60  | 60  |
|                                                     | f             | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                                                     | g             | 8   | 8   | 8   | 8   | 8   | 8   |
|                                                     | g.1           | 2   | 2   | 2   | 2   | 2   | 2   |
|                                                     | h             | 83  | 88  | 95  | 99  | 99  | 105 |
|                                                     | i             | 78  | 85  | 96  | 103 | 103 | 110 |
|                                                     | k             | 31  | 32  | 32  | 39  | 39  | 39  |
|                                                     | l             | 43  | 52  | 54  | 58  | 58  | 65  |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                                                     |               | -4  | -4  | -4  | -10 | -10 | -10 |