

Plug TM  
Part no. 24672




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- with protective cap
- (form CP)

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 5 p                                                           |
| Voltage                   | 440-460 V                                                     |
| Clock position            | 11 h                                                          |
| Hertz                     | 60 Hz                                                         |
| Connection technology     | Screw terminals                                               |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts |
| Protection type           | IP 67                                                         |
| Weight                    | 261 g                                                         |
| Declaration of Conformity | VDE, EAC                                                      |

Drawing



| Drawing<br>2 MB 240      | Amp.<br>Poles | 16   |      | 32  |     |
|--------------------------|---------------|------|------|-----|-----|
|                          |               | 3    | 5    | 4   | 5   |
| Dim. in mm               | a             | 148  | 153  | 191 | 185 |
|                          | b             | 70   | 87   | 94  | 101 |
|                          | h             | 75   | 92   | 97  | 105 |
|                          | n             | 108  | 112  | 141 | 133 |
|                          | y             | 14.5 | 16   | 22  | 22  |
| Terminal for cond. cross |               | 1    | 1    | 2.5 | 2.5 |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —6  | —6  |