

Connector TM  
Part no. 24888




- screw terminals
- frame terminals
- X-CONTACT
- rubberised grip area
- highly heat resistant contact carrier
- nickel plated contacts
- cable gland and external cable grip
- strain relief and protection against kinking
- enclosure with thread lock
- two safety slides (form DS)

Technical specifications

|                           |                                                                                                                                                      |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ampere                    | [63.0, 63.0] A                                                                                                                                       |
| Poles                     | [5.0, 5.0] p                                                                                                                                         |
| Voltage                   | 50-500, 50-500 V                                                                                                                                     |
| Clock position            | [2.0, 2.0] h                                                                                                                                         |
| Hertz                     | 300-500, 300-500 Hz                                                                                                                                  |
| Connection technology     | [ClassificationAttributeValueModel (8796126970464@9), ClassificationAttributeValueModel (8796126970464@9)]                                           |
| Contact                   | highly heat resistant contact carrier, nickel plated contacts, X-CONTACT®, highly heat resistant contact carrier, nickel plated contacts, X-CONTACT® |
| Protection type           | [ClassificationAttributeValueModel (8796126741088@33), ClassificationAttributeValueModel (8796126741088@33)]                                         |
| Weight                    | 880 g                                                                                                                                                |
| Declaration of Conformity | VDE                                                                                                                                                  |

Drawing



| Drawing<br>3 MB 68       | Amp.<br>Poles | 63  |     |     | 125 |     |     |
|--------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                          |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm               | a             | 270 | 270 | 270 | 310 | 310 | 310 |
|                          | b             | 113 | 113 | 113 | 125 | 125 | 125 |
|                          | h             | 123 | 123 | 123 | 135 | 135 | 135 |
|                          | y             | 36  | 36  | 36  | 49  | 49  | 49  |
| Terminal for cond. cross |               | 6   | 6   | 6   | 25  | 25  | 25  |
| section (mm²) min.-max.  |               | —16 | —16 | —16 | —50 | —50 | —50 |