

**Plug AM-TOP®**  
Part no. 257




- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 230 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 171 g           |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>2 MB 217                  |   | 16            |       |       | 32            |     |      |
|--------------------------------------|---|---------------|-------|-------|---------------|-----|------|
|                                      |   | Amp.<br>Poles |       |       | Amp.<br>Poles |     |      |
|                                      |   | 3             | 4     | 5     | 3             | 4   | 5    |
| Dim. in mm                           | a | 142           | 147   | 147   | 186           | 186 | 180  |
|                                      | b | 53            | 59    | 67    | 70            | 70  | 77   |
|                                      | h | 59            | 69.4  | 76    | 81            | 81  | 89.5 |
|                                      | n | 105.2         | 110.5 | 110.5 | 141           | 141 | 135  |
|                                      | y | 14.5          | 16    | 16    | 22            | 22  | 22   |
| Terminal for cond. cross             |   | 1             | 1     | 1     | 2.5           | 2.5 | 2.5  |
| section (mm <sup>2</sup> ) min.-max. |   | —2.5          | —2.5  | —2.5  | —6            | —6  | —6   |