

Panel mounted inlet  
Part no. 379




- screw terminals

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 182 g           |
| Declaration of Conformity | VDE, EAC, CQC   |

Drawing



| Drawing<br>2 MB 73<br>Dim. in mm                    | Amp.<br>Poles | 16   |      | 32  |     |     |
|-----------------------------------------------------|---------------|------|------|-----|-----|-----|
|                                                     |               | 4    | 5    | 3   | 4   | 5   |
| a                                                   |               | 85   | 85   | 75  | 75  | 75  |
| b                                                   |               | 85   | 85   | 90  | 90  | 90  |
| c                                                   |               | 75   | 79   | 87  | 87  | 90  |
| d                                                   |               | 64   | 64   | 45  | 45  | 45  |
| d1                                                  |               | 10   | 10   | 13  | 13  | 13  |
| e                                                   |               | 64   | 64   | 78  | 78  | 78  |
| f                                                   |               | 5.5  | 5.5  | 5.5 | 5.5 | 5.5 |
| g                                                   |               | 6    | 6    | 6   | 6   | 6   |
| g.1                                                 |               | 2    | 2    | 2   | 2   | 2   |
| h                                                   |               | 129  | 129  | 137 | 137 | 138 |
| l                                                   |               | 50   | 50   | 55  | 55  | 55  |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1    | 1    | 2.5 | 2.5 | 2.5 |
|                                                     |               | -2.5 | -2.5 | -6  | -6  | -6  |