

Panel mounted inlet

Part no. 391



- screw terminals

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 32 A |
| Poles | 5 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 260 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing | Amp. | 16 | | 32 | | | | |
|---|------|-------|------|-----|-----|-----|---|---|
| | | Poles | | 4 | 5 | 3 | 4 | 5 |
| 2 MB 73 | | | | | | | | |
| Dim. in mm | | | | | | | | |
| a | | 85 | 85 | 75 | 75 | 75 | | |
| b | | 85 | 85 | 90 | 90 | 90 | | |
| c | | 75 | 79 | 87 | 87 | 90 | | |
| d | | 64 | 64 | 45 | 45 | 45 | | |
| d1 | | 10 | 10 | 13 | 13 | 13 | | |
| e | | 64 | 64 | 78 | 78 | 78 | | |
| f | | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | | |
| g | | 6 | 6 | 6 | 6 | 6 | | |
| g.1 | | 2 | 2 | 2 | 2 | 2 | | |
| h | | 129 | 129 | 137 | 137 | 138 | | |
| l | | 50 | 50 | 55 | 55 | 55 | | |
| Terminal for cond. cross section (mm ²) min.-max. | | 1 | 1 | 2.5 | 2.5 | 2.5 | | |
| | | -2.5 | -2.5 | -6 | -6 | -6 | | |