

Wall mounted receptacle
Part no. 5513




- screw terminals
- suitable for through wiring
- with fixing points for terminal strip part no. 40113

Technical specifications

| | |
|---------------------------|-----------------|
| Ampere | 32 A |
| Poles | 4 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 67 |
| Weight | 806 g |
| Declaration of Conformity | EAC, CQC |

Drawing



| Drawing 1 MB 206 | Amp. Poles | 16 | | | 32 | | |
|--|---------------|---------------|------|------|---------------|------|------|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 225 | 225 | 225 | 225 | 225 | 225 |
| | b | 118 | 118 | 118 | 118 | 118 | 118 |
| | c | 144 | 150 | 152 | 155 | 155 | 159 |
| | d | 208 | 208 | 208 | 208 | 208 | 208 |
| | e | 101 | 101 | 101 | 101 | 101 | 101 |
| | f | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 | 6.3 |
| | g | 8 | 8 | 8 | 8 | 8 | 8 |
| | h | 249 | 251 | 253 | 255 | 253 | 259 |
| | M | 1x25 and 1x32 | | | 1x25 and 1x32 | | |
| | M* | 2x25 | 2x25 | 2x25 | 2x25 | 2x25 | 2x25 |
| Max. cable diam. (mm) | | 25 | 25 | 25 | 25 | 25 | 25 |
| Terminal for cond. cross section (mm²) min-max. | | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
| | | —4 | —4 | —4 | —10 | —10 | —10 |