

**EverGUM receptacle combination**  
Part no. 70009




- solid rubber enclosure, signal yellow RAL 1003
- pre-wired for installation

**Technical specifications**

|                           |                                                                                                                                    |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| CEE 32 A, 5 p, 400 V      | 1                                                                                                                                  |
| CEE 16 A, 5 p, 400 V      | 2                                                                                                                                  |
| SCHUKO® 16 A, 230 V       | 4                                                                                                                                  |
| Fusing                    | <ul style="list-style-type: none"><li>• 1 MCB 32 A, 3 p, C</li><li>• 2 MCB's 16 A, 3 p, C</li><li>• 4 MCB's 16 A, 1 p, B</li></ul> |
| Pre-fuse max.             | 80 A                                                                                                                               |
| InA                       | 72 A                                                                                                                               |
| RDF                       | 0.75                                                                                                                               |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• for 2 cables up to 5 x 25 mm²</li></ul>                                                    |
| Protection type           | IP 44                                                                                                                              |
| Shutter                   | false                                                                                                                              |
| Enclosure material        | Solid rubber                                                                                                                       |
| Weight                    | 11040 g                                                                                                                            |
| Height                    | 380 mm                                                                                                                             |
| Width                     | 320 mm                                                                                                                             |
| Declaration of Conformity | EAC                                                                                                                                |

**Drawing**



Drawing  
5 MB 41  
Dim. in mm