

Wall mounted receptacle  
Part no. 7126




- screw terminals
- fused with RCD (0.03 A)
- other leakage current ratings on request

Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 4 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Enclosure material        | Plastic         |
| Weight                    | 1434 g          |
| Declaration of Conformity | EAC, CQC        |

Drawing



| Drawing<br>1 MB 168                                 | Amp.<br>Poles | 16            |      |      | 32            |      |      |
|-----------------------------------------------------|---------------|---------------|------|------|---------------|------|------|
|                                                     |               | 3             | 4    | 5    | 3             | 4    | 5    |
| Dim. in mm                                          | a             | 225           | 225  | 225  | 225           | 225  | 225  |
|                                                     | b             | 118           | 118  | 118  | 118           | 118  | 118  |
|                                                     | c             | 141           | 141  | 141  | 146           | 146  | 146  |
|                                                     | d             | 208           | 208  | 208  | 208           | 208  | 208  |
|                                                     | e             | 101           | 101  | 101  | 101           | 101  | 101  |
|                                                     | f             | 6.3           | 6.3  | 6.3  | 6.3           | 6.3  | 6.3  |
|                                                     | g             | 8             | 8    | 8    | 8             | 8    | 8    |
|                                                     | h             | 250           | 252  | 254  | 264           | 264  | 264  |
|                                                     | M             | 1x25 and 1x32 |      |      | 1x25 and 1x32 |      |      |
|                                                     | M*            | 2x25          | 2x25 | 2x25 | 2x25          | 2x25 | 2x25 |
| Max. cable diam. (mm)                               |               | 25            | 25   | 25   | 25            | 25   | 25   |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 1.5           | 1.5  | 1.5  | 2.5           | 2.5  | 2.5  |
|                                                     |               | —4            | —4   | —4   | —10           | —10  | —10  |