

**Connector**  
Part no. 716A




- screw terminals
- with cable gland

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 20-25, 40-50 V  |
| Clock position            | 4 h             |
| Hertz                     | 100-200 Hz      |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 227 g           |
| Declaration of Conformity | EAC, CQC        |

**Drawing**



| Drawing<br>3 MB 36       | Amp.<br>Poles | 16   |      | 32   |      |
|--------------------------|---------------|------|------|------|------|
|                          |               | 2    | 3    | 2    | 3    |
| Dim. in mm               | a             | 164  | 164  | 164  | 164  |
|                          | b             | 55   | 55   | 55   | 55   |
|                          | h             | 67   | 67   | 67   | 67   |
|                          | m             | 142  | 142  | 142  | 142  |
|                          | y             | 24.7 | 24.7 | 24.7 | 24.7 |
| Terminal for cond. cross |               | 4    | 4    | 4    | 4    |
| section (mm²) min.-max.  |               | —10  | —10  | —10  | —10  |