

Wall mounted receptacle

Part no. 7313




- screw terminals
- fused with RCD (0.03 A)
- other leakage current ratings on request

Technical specifications

Ampere	32 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Enclosure material	Plastic
Weight	1362 g
Declaration of Conformity	EAC

Drawing



Diawing	Allip.		10			32	
1 MB 168	Poles	3	4	5	3	4	5
Dim. in mm	а	225	225	225	225	225	225
	b	118	118	118	118	118	118
	c	141	141	141	146	146	146
	d	208	208	208	208	208	208
	е	101	101	101	101	101	101
	f	6.3	6.3	6.3	6.3	6.3	6.3
	g.	8	8	8	8	8	8
	h	250	252	254	264	264	264
	M	1x25 and 1x32			1x25 and 1x32		
	М*	2x25	2x25	2x25	2x25	2x25	2x25
Max. cable dian	n. (mm)	25	25	25	25	25	25
Terminal for cor	nd. cross	1.5	1.5	1.5	2.5	2.5	2.5
section (mm²) m	iinmax.	-4	-4	-4	—10	—10	—10