

**Panel mounted receptacle**  
Part no. 7502




- screw terminals
- for horizontal installation
- switched
- mechanical DUO-interlock
- receptacles can be padlocked

**Technical specifications**

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 3 p             |
| Voltage                   | 110 V           |
| Clock position            | 4 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Enclosure material        | Plastic         |
| Weight                    | 510 g           |
| Declaration of Conformity | CQC             |

**Drawing**



| Drawing<br>5 MB 59 | Amp.<br>Poles | 16  |     |     | 32  |     |     |
|--------------------|---------------|-----|-----|-----|-----|-----|-----|
|                    |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm         | a             | 200 | 200 | 200 | 200 | 200 | 200 |
|                    | b             | 110 | 110 | 110 | 110 | 110 | 110 |
|                    | c             | 46  | 49  | 46  | 56  | 56  | 53  |
|                    | d             | 190 | 190 | 190 | 190 | 190 | 190 |
|                    | e             | 100 | 100 | 100 | 100 | 100 | 100 |
|                    | f             | 5   | 5   | 5   | 5   | 5   | 5   |
|                    | g             | 13  | 13  | 13  | 13  | 13  | 13  |
|                    | k max.        | 56  | 56  | 56  | 56  | 56  | 56  |
|                    |               |     |     |     |     |     |     |
|                    |               |     |     |     |     |     |     |