

**Power post**  
Part no. 84335



- from steel tube
- wall thickness 4.0 mm
- hot-dip galvanised
- powder-coated
- colour: red
- hinged supply aperture
- with safety lock
- dimensions (H x Ø): 1050 x 220 mm (inside)
- weight: approx. 45 kg
- aperture at bottom: (H x W) 50 x 40 mm
- fixing flange: Ø 360 mm
- with 4 fixing holes 15.5 mm
- for fixing to an existing fundament

**Technical specifications**

CEE 16 A, 5 p, 400 V	1
SCHUKO® 16 A, 230 V	2
Fusing	<ul style="list-style-type: none"><li>• 1 MCB 16 A, 3 p, C</li><li>• 1 MCB 16 A, 1 p, B</li></ul>
Connection / feeder cable	<ul style="list-style-type: none"><li>• for 1 cable up to 5 x 6 mm²</li></ul>
Protection type	IP 44
Shutter	false
Enclosure material	Metal
Weight	40000 g
Height	1050 mm
Diameter	220 mm
Declaration of Conformity	EAC


**Drawing**

Top view of the bottom plate



The supply aperture is located between 2 drill holes in the bottom plate

Part no. 18500RO  
Colour: red RAL 3005



Drawing  
1 MB 443  
Dim. in mm