

**AMAXX® receptacle combination**  
Part no. 910006




- pre-wired for installation
- enclosure and insert made of AMAPLAST

Technical specifications

|                           |                                |
|---------------------------|--------------------------------|
| CEE 16 A, 3 p, 230 V      | 1                              |
| SCHUKO® 16 A, 230 V       | 2                              |
| Connection / feeder cable | • for 1 cable up to 5 x 10 mm² |
| Protection type           | IP 44                          |
| Shutter                   | false                          |
| Enclosure material        | Plastic                        |
| Weight                    | 1326 g                         |
| Height                    | 130 mm                         |
| Width                     | 225 mm                         |
| Declaration of Conformity | EAC                            |

Drawing



Drawing 1 MB 531

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 25 each on top and bottom, 2 x M 20 each on top and bottom for cut out.