

**AMAXX® receptacle combination**  
Part no. 920032




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST

Technical specifications

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| SCHUKO® 16 A, 230 V       | 6                                                 |
| Connection / feeder cable | • 2 m H07RN-F5G2.5 with CEE-plug 16 A, 5 p, 400 V |
| Protection type           | IP 44                                             |
| Shutter                   | false                                             |
| Enclosure material        | Plastic                                           |
| Weight                    | 3400 g                                            |
| Height                    | 260 mm                                            |
| Width                     | 225 mm                                            |

Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.