

## Wall mounted inlet

Part no. 922




- · screw terminals
- enclosure base with stamped recess for quick cutting out

## **Technical specifications**

Ampere	16 A
Poles	4 p
Voltage	50-500 V
Clock position	2 h
Hertz	300-500 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Weight	237 g
Declaration of Conformity	EAC, CQC

## Drawing



Drawing	ing Amp.   16			32			
2 MB 32	Poles	3	4	5	3	4	5
Dim. in mm	a	87	100	100	128	128	128
	b	64	75	75	84	84	84
	c	93	106	110	133	133	135
	d	40	_	_	_	_	_
	d1	_	10.5	10.5	11	11	11
	e	50.5	59	59	68	68	68
	f	4,5	5	5	5.3	5.3	5.3
	g.	4	4	4	4	4	4
	h	122	133	135	169	169	170
	M	20	20	20	32	32	32
	M*	1x20 (blind) to be cut out			2x25 (blind) to be cut out		
Max. cable diam	n. (mm)	15	15	15	18/25	18/25	18/25
Terminal for con	d. cross	1	1	1	2.5	2.5	2.5
section (mm²) m	inmax.	-2.5	-2.5	-2.5	6	6	6