

AMAXX® receptacle combination
Part no. 930024




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

| | |
|---------------------------|---|
| SCHUKO® 16 A, 230 V | 6 |
| Fusing | • 1 RCD 40 A, 4 p, 0.03 A |
| Pre-fuse max. | 16 A |
| InA | 16 A |
| RDF | 1 |
| Connection / feeder cable | • 2 m H07RN-F5G2.5 with CEE-plug 16 A, 5 p, 400 V |
| Protection type | IP 44 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 5160 g |
| Height | 390 mm |
| Width | 225 mm |

Drawing



Drawing 1 MB 522

Depth dimensions at various fittings.

| Receptacles | Degrees | Depth |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44 | 175 mm |
| | IP 67 | 194 mm |
| CEE 16A, 3p, 230V | IP 44 | 204 mm |
| | IP 67 | 205 mm |
| CEE 16A, 5p, 400V | IP 44 | 209 mm |
| | IP 67 | 213 mm |
| CEE 32A, 5p, 400V | IP 44 | 221 mm |
| | IP 67 | 227 mm |
| CEE 63A, 5p, 400V | IP 44 | 248 mm |
| | IP 67 | 248 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.