

**AMAXX® receptacle combination**  
Part no. 930231




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

|                           |                                                                                                          |
|---------------------------|----------------------------------------------------------------------------------------------------------|
| CEE 16 A, 5 p, 400 V      | 2                                                                                                        |
| Swiss standard - Type 23  | 2                                                                                                        |
| Swiss standard - Type 25  | 1                                                                                                        |
| Fusing                    | <ul style="list-style-type: none"><li>• 1 RCD 40 A, 4 p, 0.03 A</li><li>• 2 MCB's 16 A, 3 p, C</li></ul> |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• for 2 cables up to 5 x 25 mm<sup>2</sup></li></ul>               |
| Protection type           | IP 44                                                                                                    |
| Shutter                   | false                                                                                                    |
| Enclosure material        | Plastic                                                                                                  |
| Weight                    | 5620 g                                                                                                   |
| Height                    | 390 mm                                                                                                   |
| Width                     | 225 mm                                                                                                   |

Drawing



Drawing 1 MB 522

Depth dimensions at various fittings.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 175 mm |
|                    | IP 67   | 194 mm |
| CEE 16A, 3p, 230V  | IP 44   | 204 mm |
|                    | IP 67   | 205 mm |
| CEE 16A, 5p, 400V  | IP 44   | 209 mm |
|                    | IP 67   | 213 mm |
| CEE 32A, 5p, 400V  | IP 44   | 221 mm |
|                    | IP 67   | 227 mm |
| CEE 63A, 5p, 400V  | IP 44   | 248 mm |
|                    | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.