

**AMAXX® receptacle combination**  
Part no. 970001GE




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover
- with suspension eyes on top, grip hooks on the bottom and chain set provided

Technical specifications

|                           |                                                                                                                                                                    |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CEE 32 A, 5 p, 400 V      | 1                                                                                                                                                                  |
| CEE 16 A, 5 p, 400 V      | 1                                                                                                                                                                  |
| SCHUKO® 16 A, 230 V       | 4                                                                                                                                                                  |
| Fusing                    | <ul style="list-style-type: none"><li>• 1 RCD 40 A, 4 p, 0.03 A</li><li>• 1 MCB 32 A, 3 p, C</li><li>• 1 MCB 16 A, 3 p, C</li><li>• 4 MCB's 16 A, 1 p, C</li></ul> |
| Pre-fuse max.             | 40 A                                                                                                                                                               |
| InA                       | 40 A                                                                                                                                                               |
| RDF                       | 0.75                                                                                                                                                               |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• for 1 cable up to 5 x 10 mm²</li></ul>                                                                                     |
| Protection type           | IP 44                                                                                                                                                              |
| Shutter                   | false                                                                                                                                                              |
| Enclosure material        | Plastic                                                                                                                                                            |
| Weight                    | 5000 g                                                                                                                                                             |
| Height                    | 260 mm                                                                                                                                                             |
| Width                     | 225 mm                                                                                                                                                             |

Drawing



Drawing 1 MB 630

Depth dimensions for identical configuration on both sides.

| Receptacles        | Degrees | Depth  |
|--------------------|---------|--------|
| SCHUKO® 16A, 230 V | IP 44   | 282 mm |
|                    | IP 67   | 326 mm |
| CEE 16A, 3p, 230V  | IP 44   | 342 mm |
|                    | IP 67   | 350 mm |
| CEE 16A, 5p, 400V  | IP 44   | 354 mm |
|                    | IP 67   | 362 mm |
| CEE 32A, 5p, 400V  | IP 44   | 372 mm |
|                    | IP 67   | 382 mm |

Cable entries: closed for cut out.  
1 x M 32 on top, 1 x M 25 on top and 1 x M 20 on top.