

AMAXX® receptacle combination

Part no. 970005GE




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover
- with suspension eyes on top, grip hooks on the bottom and chain set provided

Technical specifications

CEE 32 A, 5 p, 400 V	1
CEE 16 A, 5 p, 400 V	1
SCHUKO® 16 A, 230 V	3
Data port sockets	1 Cepex RJ45, 2 fold Cat.6
Fusing	• 1 RCD 40 A, 4 p, 0.03 A • 1 MCB 16 A, 3 p, C • 3 MCB's 16 A, 1 p, C
Pre-fuse max.	32 A
InA	32 A
RDF	1
Connection / feeder cable	• for 1 cable up to 5 x 10 mm²
Protection type	IP 44
Shutter	false
Enclosure material	Plastic
Weight	5000 g
Height	260 mm
Width	225 mm

Drawing



Drawing 1 MB 630

Depth dimensions for identical configuration on both sides.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	282 mm
	IP 67	326 mm
CEE 16A, 3p, 230V	IP 44	342 mm
	IP 67	350 mm
CEE 16A, 5p, 400V	IP 44	354 mm
	IP 67	362 mm
CEE 32A, 5p, 400V	IP 44	372 mm
	IP 67	382 mm

Cable entries: closed for cut out.
1 x M 32 on top, 1 x M 25 on top and 1 x M 20 on top.