

Connector StarTOP® with SafeCONTACT
Part no. 980




- screwless, with insulation displacing technique
- [X-CONTACT](#)
- cable gland and sealing
- strain relief and protection against kinking
- enclosure with thread lock and safety slide
- for use on camping sites, please select type 180AC

Technical specifications

| | |
|---------------------------|-------------------------|
| Ampere | 16 A |
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screwless - SafeCONTACT |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 186 g |
| Declaration of Conformity | VDE, EAC, CQC |

Drawing



| Drawing 3 MB 60 | Amp. Poles | 16 | | | 32 | | |
|--------------------------|---------------|------|------|------|-----|-----|-----|
| | | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 160 | 174 | 172 | 214 | 214 | 210 |
| | b | 57 | 61 | 69 | 75 | 75 | 80 |
| | h | 83 | 92 | 98 | 100 | 100 | 108 |
| | y | 16 | 16 | 16 | 22 | 22 | 22 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max. | | —2.5 | —2.5 | —2.5 | —6 | —6 | —6 |