

**Plug PowerTOP® Xtra R with ErgoCONTACT**  
Part no. 13600




- screw terminals [ErgoCONTACT](#)
- highly heat resistant contact carrier
- nickel plated contacts
- ergonomic enclosure design with nubbed grip areas
- rubberised cable gland with sealing
- strain relief and protection against kinking
- thread lock and safety slide
- area for self-adhesive labels

Technical specifications

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Ampere                    | 16 A                                                          |
| Poles                     | 5 p                                                           |
| Voltage                   | 400-440 V                                                     |
| Clock position            | 11 h                                                          |
| Hertz                     | 50-60 Hz                                                      |
| Connection technology     | Screw terminals, ErgoCONTACT®                                 |
| Contact                   | nickel plated contacts, highly heat resistant contact carrier |
| Protection type           | IP 54                                                         |
| Weight                    | 195 g                                                         |
| Declaration of Conformity | VDE, EAC                                                      |

Drawing



| Drawing<br>2 MB 253      | Amp.<br>Poles | 16   |      | 32   |
|--------------------------|---------------|------|------|------|
|                          |               | 3    | 5    | 5    |
| Dim. in mm               | a             | 154  | 163  | 196  |
|                          | b             | 55   | 68   | 78   |
|                          | h             | 58   | 74   | 86   |
|                          | n             | 118  | 122  | 151  |
|                          | y             | 15   | 17.2 | 24.7 |
| Terminal for cond. cross |               | 1    | 1    | 2.5  |
| section (mm²) min.-max.  |               | —2.5 | —2.5 | —6   |