

Connector PowerTOP® Xtra R with ErgoCONTACT

Part no. 14565




- screw terminals [ErgoCONTACT](#)
- [X-CONTACT](#)
- highly heat resistant contact carrier
- nickel plated contacts
- ergonomic enclosure design with nubbed grip areas
- rubberised cable gland with sealing
- strain relief and protection against kinking
- thread lock and safety slide
- area for self-adhesive labels

Technical specifications

| | |
|---------------------------|---|
| Ampere | 16 A |
| Poles | 5 p |
| Voltage | 50-500 V |
| Clock position | 10 h |
| Hertz | 100-300 Hz |
| Connection technology | Screw terminals, ErgoCONTACT® |
| Contact | nickel plated contacts, X-CONTACT®, highly heat resistant contact carrier |
| Protection type | IP 54 |
| Weight | 215 g |
| Declaration of Conformity | VDE, EAC |

Drawing



| Drawing 3 MB 79 | Amp. Poles | 16 | | 32 |
|--------------------------------------|---------------|------|------|------|
| | | 3 | 5 | 5 |
| Dim. in mm | a | 166 | 174 | 209 |
| | b | 57 | 69 | 80 |
| | h | 83 | 98 | 108 |
| | y | 15 | 17.2 | 24.7 |
| Terminal for cond. cross | | 1 | 1 | 2.5 |
| section (mm ²) min.-max. | | -2.5 | -2.5 | -6 |