

Connector PowerTOP® Xtra R with ErgoCONTACT
Part no. 14601




- screw terminals [ErgoCONTACT](#)
- [X-CONTACT](#)
- highly heat resistant contact carrier
- nickel plated contacts
- ergonomic enclosure design with nubbed grip areas
- rubberised cable gland with sealing
- strain relief and protection against kinking
- thread lock and safety slide
- area for self-adhesive labels

Technical specifications

| | |
|---------------------------|---|
| Ampere | 16 A |
| Poles | 5 p |
| Voltage | Isolating transformer |
| Clock position | 12 h |
| Connection technology | Screw terminals, ErgoCONTACT® |
| Contact | nickel plated contacts, X-CONTACT®, highly heat resistant contact carrier |
| Protection type | IP 54 |
| Weight | 215 g |
| Declaration of Conformity | VDE, EAC |

Drawing



| Drawing | Amp. | 16 | 32 |
|--------------------------|-------|------|------|
| 3 MB 79 | Poles | 3 | 5 |
| Dim. in mm | a | 166 | 174 |
| | b | 57 | 69 |
| | h | 83 | 98 |
| | y | 15 | 17.2 |
| Terminal for cond. cross | | 1 | 1 |
| section (mm²) min.-max. | | —2.5 | —2.5 |