

DELTA-BOX receptacle combination

Part no. 92894




- pre-wired for installation
- with cable grip and installed hanging hook enclosure and insert made of AMAPLAST

Technical specifications

CEE 16 A, 5 p, 400 V	1
CEE 16 A, 3 p, 230 V	1
SCHUKO® 16 A, 230 V	1
Connection / feeder cable	 for 1 cable up to 5 x 6 mm²
Protection type	IP67
Shutter	false
Enclosure material	Plastic
Weight	962 g
Declaration of Conformity	EAC

Drawing





3 MB 45			
Pos.	Receptacles	IP-degrees	Dim.
a			114.0 mm
a1	SCHUKO®, 16 A, 230 V	IP 68	35.0 mm
a1	CEE 16 A, 3 p, 230 V	IP 67	56.3 mm
a1	CEE 16 A, 5 p, 400 V	IP 67	59.0 mm
a2			30.0 mm
b			160.0 mm
b1	SCHUKO®, 16 A, 230 V	IP 44	24.0 mm
b1	CEE 16 A, 3 p, 230 V	IP 44	44.3 mm
b1	CEE 16 A, 5 p, 400 V	IP 44	47.0 mm
C			133.0 mm
d			97.0 mm
1/			17.0 mm