

DELTA-BOX receptacle combination

Part no. 92915




- pre-wired for installation
- with internal strain relief and installed hanging hook
- enclosure and insert made of **AMAPLAST**

Technical specifications

| | |
|---------------------------|---|
| CEE 16 A, 5 p, 400 V | 1 |
| SCHUKO® 16 A, 230 V | 2 |
| Connection / feeder cable | • for 1 cable up to 5 x 6 mm ² |
| Protection type | IP44 |
| Shutter | false |
| Enclosure material | Plastic |
| Weight | 792 g |
| Declaration of Conformity | EAC, CQC |

Drawing



| Pos. | Receptacles | IP-degrees | Dim. |
|------|----------------------|------------|--------------|
| a | | | 114.0 mm |
| a1 | SCHUKO®, 16 A, 230 V | IP 44 | max. 30.0 mm |
| a1 | CEE 16 A, 3 p, 230 V | IP 44 | 52.7 mm |
| a1 | CEE 16 A, 5 p, 400 V | IP 44 | 50.5 mm |
| a1 | CEE 32 A, 5 p, 400 V | IP 44 | 64.0 mm |
| a2 | | | 30.0 mm |
| b | | | 160.0 mm |
| b1 | SCHUKO®, 16 A, 230 V | IP 44 | max. 18.0 mm |
| b1 | CEE 16 A, 3 p, 230 V | IP 44 | 42.0 mm |
| b1 | CEE 16 A, 5 p, 400 V | IP 44 | 40.0 mm |
| b1 | CEE 32 A, 5 p, 400 V | IP 44 | 53.2 mm |
| c | | | 133.0 mm |
| d | | | 97.0 mm |
| y | | | 17.0 mm |