

## Wall mounted receptacle

Part no. 7312



- screw terminals
- fused with RCD (0.03 A)
- other leakage current ratings on request

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 5 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Enclosure material        | Plastic         |
| Weight                    | 1386 g          |
| Declaration of Conformity | CN,CQC          |

## Drawing



| Drawing<br>1 MB 168 | Amp.<br>Poles   | 16            |      |      | 32            |      |      |
|---------------------|---|---------------|------|------|---------------|------|------|
|                     |   | 3             | 4    | 5    | 3             | 4    | 5    |
| Dim. in mm          | a   | 225           | 225  | 225  | 225           | 225  | 225  |
|                     | b   | 118           | 118  | 118  | 118           | 118  | 118  |
|                     | c   | 141           | 141  | 141  | 146           | 146  | 146  |
|                     | d   | 208           | 208  | 208  | 208           | 208  | 208  |
|                     | e   | 101           | 101  | 101  | 101           | 101  | 101  |
|                     | f   | 6.3           | 6.3  | 6.3  | 6.3           | 6.3  | 6.3  |
|                     | g   | 8             | 8    | 8    | 8             | 8    | 8    |
|                     | h   | 250           | 252  | 254  | 264           | 264  | 264  |
|                     | M   | 1x25 and 1x32 |      |      | 1x25 and 1x32 |      |      |
|                     | M*  | 2x25          | 2x25 | 2x25 | 2x25          | 2x25 | 2x25 |
|                     | Max. cable diam. (mm)   | 25            | 25   | 25   | 25            | 25   | 25   |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5           | 1.5  | 1.5  | 2.5           | 2.5  | 2.5  |
|                     |   | -4            | -4   | -4   | -10           | -10  | -10  |