

# AMTRON® 4You 510 11 C2

For charging electric vehicles in private areas



**MENNEKES**  
Elektrotechnik GmbH & Co. KG

Aloys-Mennekes-Straße 1  
57399 Kirchhundem  
GERMANY

[www.MENNEKES.org](http://www.MENNEKES.org)

# Equipment features

## General

- Mode 3 charging (IEC 61851-1)
- Plugs and sockets according to IEC 62196-2
- Prepared for ISO 15118
- Maximum charging power: 11 kW
- Connection: 1-phase / 3-phase
- Max. charging power configurable by qualified electrician
- LED status indicator
- Switching of charging modes via button on the wallbox
- Proximity sensor
- Bottom lighting
- Energy saving mode for reduced standby consumption
- Permanently connected charging cable with type 2 (7.5 m)
- Integrated cable hanger
- Interchangeable Front Cover
- Color: arctic white

## APP

- AMTRON® 4Drivers app for the end customer (available free of charge)
  - For authorization, control and visualization of charging processes
  - Display of the charged energy quantity and energy costs
  - Data export of all charging processes in PDF and CSV format
  - User and RFID management
- AMTRON® 4Installers app for the installer (available free of charge)
  - For easy installation of the charging station

## Authorisation options

- Autostart (without authorisation)
- AMTRON® 4Drivers App
- RFID (ISO / IEC 14443 A/B)  
Compatible with MIFARE classic and MIFARE DESFire
- Via a backend system

## Networking options

- Connection to a network via LAN / Ethernet (RJ45)
- Connection to a network via WLAN / WiFi

## Options for connecting to a backend system

- Via LAN / Ethernet (RJ45) and an external router
- Support for OCPP 1.6j communication protocols

## Options for local load management

- Reduction of the charging current using an external switching contact (downgrade input)
- Static load management
- Reduction of the charging current in case of uneven phase load (unbalanced load limitation)
- Solar charging via an upstream, external energy meter
  - 1- / 3-phase solar charging for charging powers from 1.4 - 11 kW incl. dynamic phase switching
- Local blackout by connecting an external Modbus TCP energy meter

## Options for connecting to an external energy management system (EMS)

- Via Modbus TCP
- Via EEBus
- Dynamic control of the charging current via an OCPP system (smart charging)

## Integrated protective devices

- DC residual current monitoring > 6 mA in accordance with IEC 62955
- Residual current circuit breaker must be installed upstream
- Circuit breaker must be installed upstream
- Switching output for controlling an external shunt release, in order to disconnect the charging point voltage from the mains in case of a fault (welded load contact, welding detection)

## Technical data

AMTRON® 4You 510 11 C2		1315001205WH
Max. charging power Mode 3 [kW]	Charging point 1	11
Connection	Charging point 1	1-phase / 3-phase
Rated current $I_{nA}$ [A]		16
Rated current of a Mode 3 $I_{nC}$ charging point [A]		16
Rated voltage $U_N$ [V] AC $\pm 10\%$		230 / 400
Rated frequency $f_N$ [Hz]		50
Max. back-up fuse [A]		20
Rated insulation voltage $U_i$ [V]		500
Rated impulse withstand voltage $U_{imp}$ [kV]		4
Conditional rated short-circuit current $I_{CC}$ [kA]		1.1
Rated diversity factor RDF		1
Types of system earthing		TN/TT
EMC classification		A+B
Protection class		I
IP rating		IP54
Overvoltage category		III
Mechanical impact protection		IK10
Contamination rating		3
Installation		open air, interior
Stationary / Mobile		fixed
Use (according to IEC 61439-7)		ACSEV
External design		wall mounting
Dimensions H x W x D [mm]		402.2 x 226.3 x 168.2
Weight [g]		5500
Standard		IEC 61851, IEC 61439-7

The specific standards according to which the product was tested can be found in the declaration of conformity for the product.

# Technical data

## Permissible ambient conditions

	Min.	Max.
Ambient temperature [°C]	-30	50
Average temperature over 24 hours period [°C]		35
Altitude [m above sea level]		2000
Relative humidity [%]		95

## Technical data

### Supply line terminal strip

Number of terminals	5	
Conductor material	Copper	
	Min.	Max.
Clamping range - rigid [mm <sup>2</sup> ]	0.2	10
Clamping range - flexible [mm <sup>2</sup> ]	0.2	10
Clamping range with ferrule [mm <sup>2</sup> ]	0.2	6
Tightening torque [Nm]	0.8	1.6


### Downgrade input terminals

Number of terminals	2	
	Min.	Max.
Clamping range - rigid [mm <sup>2</sup> ]	0.5	4
Clamping range - flexible [mm <sup>2</sup> ]	0.5	4
Clamping range with ferrule [mm <sup>2</sup> ]	0.5	2.5
Tightening torque [Nm]	-	-

### Switching output für shunt release terminals

Number of terminals	2	
Max. switching voltage [V] AC	230	
Max. switching voltage [V] DC	24	
Max. switching current [A]	1	
	Min.	Max.
Clamping range - rigid [mm <sup>2</sup> ]	0.5	4
Clamping range - flexible [mm <sup>2</sup> ]	0.5	4
Clamping range with ferrule [mm <sup>2</sup> ]	0.5	2.5
Tightening torque [Nm]	-	-

# Dimensional drawing



# Example

